Technical data sheet





COUGAR 8450 SEMI SYNTHETIC BOOM GREASE

Cougar 8450 Semi Synthetic Boom Grease is a highly adhesive, water resistant, extreme pressure grease especially designed to provide superior lubrication to wear pads on mobile crane telescopic booms, and lattice cranes.

Cougar 8450 which incorporates a unique semi synthetic base oil formulation incorporates advanced technology additives to lubricate and protect sliding surfaces, reducing friction and wear, extending wear pad life and re-lubrication intervals.

Cougar 8450 is a truly versatile lubricant: other applications include open gears, tower hoist rack and pinions, crane turntables and external wire ropes.

TYPICAL CHARACTERISTICS

Grade	8450
NLGI Grade	0 / 1
Colour	Dark Red
Texture	Highly Adhesive
Base Thickener	Lithium
Dropping Point °C	>170
Four Ball (ASTM D2596), Weld Load	315 KGS

FEATURES & BENEFITS

- Extreme Pressure- Reduces friction & wear, extends wear pad life.
- Water Resistant- Seals out moisture and prevents rust and corrosion.
- Highly Adhesive- extends re-lubrication intervals. Does not drip on windscreens and chassis when applied correctly.
- Reduces Labour Easy to apply with either brush or roller. Safer to apply even at extreme heights.
- Reduces Juddering- Increases lubricity provides smoother surface contact between wear pads and boom section.





QMS^o ISO 9001 : 2015 REGISTERED Telephone: 0203 011 5575 www.cougar-lubricantsint.com Cougar Lubricants International Ltd. Registered in England No. 08401804

This product information is correct at the time of print, Cougar Lubricants International Ltd reserves the right to alter product names and specifications at any time without notice. For the latest information please contact your Cougar Supplier.